



MOBILE BENCH IRRIGATION

- ✓ Flexible irrigation system
- ✓ Built-in final emptying construction
- ✓ Enables easy transport of the benches around in the nursery



Flexible irrigation for mobile bench systems

A mobile bench system must enable easy transport of the container benches around in the nursery, for example using conveyor tracks or a crane. To meet this need, DGT by Senmatic has developed an irrigation system specially for the mobile bench system, which makes it possible to move the container benches without consideration for the water installation.

Water filling

A special triangle valve ensures that water filling is carried out in a splash-less jet. The triangle valve is easily mounted with a special bracket on the drain edge.

The triangle valve and the special bracket are designed so that the container bench pushes the valve sideways when lifted by a crane, without damaging the valve or the container bench.

Draining

For the quick and efficient draining of water, we have developed the HV siphon valve. With the built-in final emptying construction, the last of the water is able to run out after the siphon effect has stopped. This is also an advantage if there is a lot of dirt on the benches.

The siphon valve is adjustable in steps for optional water filling height.



SPECIFICATIONS / MOBILE BENCH IRRIGATION

Iphon valve HV 3

Draining:	4 or 9 L/min
Final emptying:	0.2 L/min
Draining height (adjustable):	45 - 60 mm (above sump bottom)
Mounting hole in sump:	Min. 26 mm - max. 30 mm
Mounting thread:	3/4" RG
Closing function:	Yes
Material (valve):	Black nylon
Weight (total):	50 g (0.11 lb)
Length:	100 mm (0.39")

Triangle valve - 8 x 6 mm

Capacity (recommended):	8 - 14 L/min
Water pressure (recommended):	1.3 - 3.3 bar
Material:	Black nylon
Length (complete):	650 mm
Weight (complete):	Approx. 350 g (0.77 lb) incl. bracket
Bracket for mounting on the edge:	90° C or 110° C
Resistance tube:	Ø 8 x 6 mm (0.3 x 0.23"), 2 m (77")

Triangle valve - 10.5 x 8 mm

Capacity (recommended):	12 - 20 L/min
Water pressure (recommended):	1.3 - 3.3 bar
Material:	Black nylon
Length (complete):	650 mm
Weight (complete):	Approx. 350 g (0.77 lb) incl. bracket
Bracket for mounting on the edge:	90° C or 110° C
Resistance tube:	Ø 10.5 x 8 mm (0.4 x 0.3"), 1.5 m (59")

Distributor:

Version: 02112023

Contact details:

DGT by Senmatic
Phone: +45 64 89 22 11
dgtsales@senmatic.com - www.senmatic.dk

Head office:

Senmatic A/S - Industrivej 8 - DK-5471 Sønderlø